

Serial Matrix Printers

Impact solutions for industrial
and logistic environments

Highlights

- Fast, quiet, reliable printing at up to 900 characters per second¹ on up to 8 part forms³
- Reduce the need for user interventions with a reliable, heavy-duty design and Remote Printer Management Capabilities
- Boost productivity with support for dual paper paths, auto forms loading, auto thickness adjustment, auto eject & restore and more
- 24-Pin Printhead with 800 Million Character Life
- Pedestal or desktop configuration
- Superior performance in for On-Demand and Volume applications
- Unique “X” design for easy forms loading

A Leading Edge Printer For Today And Tomorrow

Designed for high output performance in the most demanding print environments – from the office to the warehouse – the **Compuprint** 9080 industrial strength printer provides professional reliability at a low cost of ownership. With an impressive functional lifetime, low per-page cost, and worry free operation, impact printers from **Compuprint** integrate the latest technology and innovation based on more than 30 years of leadership. It represents the preferred choice for business and industrial printing applications requiring up to a 57,000² pages per month workload.

Focus On Performance And Uptime

The **Compuprint** 9080 is designed with state-of-the art technologies and innovative functionalities. With print speeds up to 900 cps¹, and up to two straight continuous form paper paths for outstanding paper feeding reliability. Optional dual front paper paths and heavy-duty 6-pin tractors provide easy forms loading and support for printing on a wide range of media types. All with the superb reliability of 20,000 hours of MTBF.

CompuprintPlus.com
1-866-430-6202
sales@compuprintplus.com

Compuprint
9080



Boost Efficiency With Remote Printer Management

The NetViewMaster® Remote Printer Management Utility, included with the optional Ethernet controller, gives users visibility to a real-time printer status for every printer on the network, remote configuration of multiple printers simultaneously, and remote full function access to a virtual operator panel.

Increase Productivity With Fewer User Interventions

The combination of paper parking, switching and linking can help you maximize your printing options and increase productivity. The all-points-addressable graphics capability enables quality printing of bar codes, logos, overlays and more. Automatic forms loading and thickness adjustment, along with customizable intelligent forms handling enable highly efficient forms loading and retrieval.

Adaptable To Your Business Needs

The **Compuprint** 9080 is available in a wide variety of interface configurations including parallel, serial, USB and ethernet. Operators will appreciate the multi-lingual LCD display and intuitive, easy-to-use operator panel. The optional matching printer stand completes the solution and simplifies setup and location choices.

USPS Intelligent Mail Barcode

The US Postal Service new bar code standard will require this compatibility to take advantage of the best rates available.



Sample Intelligent Mail Barcode

COMPUPRINT

WE PRINT YOUR IDEAS

Printing Technology	24 Pin serial dot matrix printer – 136 columns @ 10 cpi																								
Throughput	660 pages per hour (ECMA 132)																								
Printing Speed (CPS)¹	<table border="1"> <thead> <tr> <th></th> <th>10 cpi</th> <th>12 cpi</th> <th>15 cpi</th> </tr> </thead> <tbody> <tr> <td>HSD</td> <td>900</td> <td></td> <td></td> </tr> <tr> <td>Draft</td> <td>800</td> <td>780</td> <td>975</td> </tr> <tr> <td>Best Draft</td> <td>400</td> <td>480</td> <td>600</td> </tr> <tr> <td>NLQ</td> <td>260</td> <td>315</td> <td>400</td> </tr> <tr> <td>LQ</td> <td>133</td> <td>160</td> <td>200</td> </tr> </tbody> </table>		10 cpi	12 cpi	15 cpi	HSD	900			Draft	800	780	975	Best Draft	400	480	600	NLQ	260	315	400	LQ	133	160	200
	10 cpi	12 cpi	15 cpi																						
HSD	900																								
Draft	800	780	975																						
Best Draft	400	480	600																						
NLQ	260	315	400																						
LQ	133	160	200																						
Paper Handling	Continuous form: front loading - Fanfold width 76 to 432 mm (3 to 17 inches), length 76 to 610 mm (3 to 24 inches) Standard: Front push tractor 6 pin Optional: Additional front push tractor 6 pin, Paper Pedestal																								
Copies³	1 + 7 – max thickness 0.635 mm (0.025 inches)																								
Special Functions	Automatic paper path switching via operator panel or SW commands, Automatic Gap Adjustment (AGA) of print head based on paper thickness, Automatic fanfold position (zero tear-off), Automatic paper parking of continuous form																								
Graphic Resolution (dpi)	Horizontal: 60, 80, 90, 120, 180, 240, 360 Vertical: 60, 72, 180, 360																								
Vertical Spacing	6 - 8 - 12 lines per inch; 3 - 4 - 6 - 8 - 12 lines per 30 mm.; n/60, n/72, n/144, n/180, n/216, n/360																								
Horizontal Spacing	10, 12, 15, 17.1, 20 cpi and proportional																								
Barcodes	UPC-A, UPC-E, EAN-8, EAN-13, UPC/EAN ADD-ON 5, UPC/EAN ADD ON 2, Code 39, Code 128, Code 11, Code 93, MSI, Postnet, Codabar, 2/5 Interleaved, 2/5 Matrix, 2/5 Industrial, Code GP, C25-3BAR, Code BCD, 2/5 Bidirectional, Intelligent Mail Barcode																								
Character Set	Standard PC IBM character sets: CS1, CS2 ; 13 EPSON national variations IBM and EPSON character sets: CP 437 (USA), CP437G (Greek), CP437SL (Slavic), CP850 (Multilingual), CP851 (Greek), CP852 (Eastern Europe), CP853 (Turkish), CP855 (Cyrillic), CP857 (Turkish), CP858 (Euro PC Multilingual), CP860 (Portugal), CP862 (Hebrew), CP863 (French-Canadian), CP864 (Arabic), CP865 (Danish-Norwegian), CP866 (Russian), CP867 (Turkish2), CP876 (OCR-A), CP877 (OCR-B), CP1098 (Farsi), CP1250 (Latin2 Windows), CP1251 (Cyrillic Windows), CP1252 (Latin1 Windows), CP1253 (Greek Windows), CP1254 (Turkish Windows), CP1255 (Hebrew Windows), CP1256 (Arabic Windows), CP1257 (Baltic Windows), 96Greek, GOST, TASS, MAZOWIA, KOI8-U, UKRANIAN, Farsi 1, Farsi 2 ISO character sets: 8859/1 (Latin1), 8859/2 (Latin2), 8859/3 (Latin3), 8859/4 (Latin4), 8859/5 (Latin/Cyrillic), 8859/6 (Latin/Arabic), 8859/7 (Latin/Greek), 8859/8 (Latin/Hebrew), 8859/9 (Latin5), 8859/15 (Latin9) DEC PPL2 character sets																								
Resident Font	Draft, Courier, Gothic, Prestige, Present, Script, OCR-A, OCR-B																								
Resident Emulations	Epson ® ESC/P LQ Series, IBM ® Proprinter XL24, IBM ® Personal Printer 2391, ANSI, DEC PPL2, Compuprint Native Commands																								
Interfaces	Parallel - Ethernet 10/100 or Parallel - Serial - USB 2.0																								
Drivers and SW	Windows 9X/2000/XP/Vista/Windows 7/Windows 8 – Plug & Play NetViewMaster (remote printer management SW) and Internal WEB Page (both available with LAN interface)																								
Print Head Life	800 Million Character Yield																								
Ribbon Life²	25 Million Character Yield – Black Ribbon																								
Memory	128KB																								
Environmental Conditions	Relative Humidity: 8% to 80% RH Temperature: 50° to 105°F (10° to 40.6°C)																								
Noise Level	54 dBA																								
Power Supply	100V - 240V (60 Hz - 50 Hz), Selectable																								
Power Consumption	116 W Max. (printing), 22 W (standby)																								
Workload	57,000 pages per month																								
Physical Dimensions & Weight	26.4" x 15.4" x 12.6" (670 mm x 390 mm x 320 mm) (WxDxH), 46.3 lb./21 kg (weight)																								
Warranty	1-Year Onsite, Next Business Day																								

CompuprintPlus.com
1-866-430-6202
sales@compuprintplus.com



Ordering Information

Printers and Supplies

Compuprint 9080 – Par/Ser/USB	PRTN9080
Compuprint 9080 – Par/Ethernet	PRTN9080N
Black Ribbon, 25MC Yield	57P1743-C

Options

Upper Tractor Assembly for Dual Paper Feed – 6 pin	44D8978-C
Open Pedestal Print Stand	44D8973-C

Extended Warranty

1 Year Extended Warranty (Onsite NBD, 9x5; Year 2)	980EXWTY1
2 Year Extended Warranty (Onsite NBD, 9x5; Year 2 & 3)	980EXWTY2
1 Year Post Warranty (Onsite NBD, 9x5)	980POSTW1
2 Year Post Warranty (Onsite NBD, 9x5)	980POSTW2

The information contained in this document is subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners.

Copyright 2010© Compuprint

¹ Exact speed varies depending on document complexity, system configuration, software application, driver and printers state. ² Actual ribbon life is dependent upon many factors, including printer configuration, machine settings, paper quality and bar code requirements. ³ Actual number of copies may vary. Paper is a highly variable medium and should be tested prior to purchase.